## WHAT IS CLAIMED IS:

1. A head-protecting airbag normally folded and housed in an upper edge of windows inside a vehicle, and deployable downward from the upper edge of windows upon inflow of inflation gas to cover the vehicle's inner side of the windows, the airbag comprising:

a vehicle's inner side wall and a vehicle's outer side wall, the walls separating from each other upon inflation of the airbag; and

a tether, the tether being joined to the vehicle's inner side wall and the vehicle's outer side wall internally of the airbag such that the tether regulates a clearance between the inner side wall and the outer side wall as the airbag is completely inflated,

a joint portion of the tether to the vehicle's inner side wall being located at lower level than a joint portion of the tether to the vehicle's outer side wall as viewed in a vertical section taken along the vehicle's transverse direction.

20

5

10

15

- 2. The head-protecting airbag according to Claim 1, wherein a lower portion of the airbag below the tether is a substantial protection area of an occupant's head.
- 25 3. The head-protecting airbag according to Claim 1, wherein

the tether comprises a through hole between the joint portions to the vehicle's inner side wall and the outer side wall, the hole communicating upper side with lower side of the tether.

5 4. The head-protecting airbag according to Claim 3, wherein: the tether is disposed along the front-rear direction of vehicle; and

the tether includes a plurality of the through holes arranged intermittently along the front-rear direction of vehicle.

5. The head-protecting airbag according to Claim 1, wherein: the airbag is formed into bag shape by sewing work; and the tether is joined to the vehicle's inner side wall and the vehicle's outer side wall by sewing work.

15

20

25

6. The head-protecting airbag according to Claim 5, wherein:
the airbag comprises a body cloth as a constituent part
for constituting the vehicle's inner side wall and the vehicle's
outer side wall, the body cloth having a shape in which the
vehicle's inner side wall and the outer side wall are connected
at lower ends of each other; and

the bag shape of the airbag is formed by folding the body cloth in two on a fold located at a position to be the lower end of the airbag, and sewing up the overlapped outer peripheries

of the cloth.